WHAT IS CLAIMED IS

- 1. A supporting disk for a surface grinding wheel, comprising a glass-fiber reinforced phenolic resin body, which includes
- 5 one of an upper covering layer (6) of a textile glass fabric (9) and a glassyarn layer (10);

an intermediate layer (7) of a fiber mat (14); and one of a lower covering layer (8) of a textile glass fabric (9) and a glassyarn layer (10).

10

15

- A supporting disk according to claim 1, wherein the intermediate layer
 is a fiber fleece.
- A supporting disk according to claim 1, wherein the intermediate layer
 is a fabric of a volume enlarged by needling.
 - A supporting disk according to claim 1, wherein the intermediate layer
 is comprised of natural fibers.
- 20 5. A supporting disk according to claim 1, wherein the intermediate layer (7) is comprised of synthetic organic fibers.
 - 6. A supporting disk according to claim 1, wherein the intermediate layer
 (7) is comprised of textile glass fibers.

25

7. A supporting disk according to claim 1, wherein the upper covering layer (6), the intermediate layer (7) and the lower covering layer (8) are sewn together.

25

- 8. A supporting disk according to claim 1, wherein the textile glass fabric (9) and the glass-yarn layer (10) are comprised of warp threads (11) and weft threads (12) which are glass-fiber rovings.
- 5 9. A supporting disk according to claim 1, wherein the intermediate layer (7) is thicker than the upper covering layer (6) and the lower covering layer (8).
- 10. A supporting disk according to claim 1, wherein the upper covering layer (6) and the lower covering layer (8) have a higher tensile strength than the intermediate layer (7).
 - 11. A surface grinding wheel comprising a supporting disk (1) and abrasive laminas (2) fixed to the supporting disk (1), the supporting disk (1) comprising
- 15 prising a glass-fiber reinforced phenolic resin body, which includes one of an upper covering layer (6) of a textile glass fabric (9) and a glassyarn layer (10); an intermediate layer (7) of a fiber mat (14); and
- 20 one of a lower covering layer (8) of a textile glass fabric (9) and a glassyarn layer (10).
 - 12. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is a fiber fleece.
 - 13. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is a fabric of a volume enlarged by needling.

- 14. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is comprised of natural fibers.
- 15. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is comprised of synthetic organic fibers.
 - 16. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is comprised of textile glass fibers.
- 10 17. A surface grinding wheel according to claim 11, wherein the upper covering layer (6), the intermediate layer (7) and the lower covering layer
 (8) are sewn together.
- 18. A surface grinding wheel according to claim 11, wherein the textile glass fabric (9) and the glass-yarn layer (10) are comprised of warp threads (11) and weft threads (12) which are glass-fiber rovings.
 - 19. A surface grinding wheel according to claim 11, wherein the intermediate layer (7) is thicker than the upper covering layer (6) and the lower covering layer (8).
 - 20. A surface grinding wheel according to claim 11, wherein the upper covering layer (6) and the lower covering layer (8) have a higher tensile strength than the intermediate layer (7).

20